

# NOKAI NT-IIIAS

ENHANCED HARD ANTI-REFLECTION MULTI-COATED LENS

EZC Silcrete® Super Hydrophobic Top Coat



## POWER RANGE

CYLINDER						CYLINDER														
-1.00	-0.75	-0.50	-0.25	0.00	SPH	SPH	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	
					0.00	-2.00														
					0.25	-2.25														
					0.50	-2.50														
					0.75	-2.75														
					1.00	-3.00														
					1.25	-3.25														
					1.50	-3.50														
					1.75	-3.75														
					2.00	-4.00														
					2.25	-4.25														
					2.50	-4.50														
					2.75	-4.75														
					3.00	-5.00														
					3.25	-5.25														
					3.50	-5.50														
					3.75	-5.75														
					4.00	-6.00														
					-6.25															
					-6.50															
					-6.75															
					-7.00															
					-7.25															
					-7.50															
					-7.75															
					-8.00															

INDEX: 1.6  
 ABBE VALUE: 42  
 SPECIFIC GRAVITY: 1.34  
 DESIGN: ASPHERIC  
 UV400NM HMC LENS

	REGULAR POWER RANGE MINUS SPHERE
	REGULAR POWER RANGE PLUS SPHERE
	EXTENDED POWER RANGE

E & O.E.