

NOKAI NT-II N-1.56 SHMC

Super Hard Multicoated Anti-Reflection Lens

S. G. DIA.



POWER RANGE

CYLINDER										CYLINDER																			
-2.00	-1.75	-1.50	-1.25	-1.00	-0.75	-0.50	-0.25	0.00	SPH	SPH	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	4.00		
									0.00	0.00																			
									0.25	-0.25																			
									0.50	-0.50																			
									0.75	-0.75																			
									1.00	-1.00																			
									1.25	-1.25																			
									1.50	-1.50																			
									1.75	-1.75																			
									2.00	-2.00																			
									2.25	-2.25																			
									2.50	-2.50																			
									2.75	-2.75																			
									3.00	-3.00																			
									3.25	-3.25																			
									3.50	-3.50																			
									3.75	-3.75																			
									4.00	-4.00																			
									-4.25																				
									-4.50																				
									-4.75																				
									-5.00																				
									-5.25																				
									-5.50																				
									-5.75																				
									-6.00																				
									-6.25																				
									-6.50																				
									-6.75																				
									-7.00																				
									-7.25																				
									-7.50																				
									-7.75																				
									-8.00																				
									-8.25																				
									-8.50																				
									-8.75																				
									-9.00																				

REGULAR POWER RANGE

EXTENDED POWER RANGE

REGULAR POWER RANGE

INDEX:	1.56
ABBE VALUE:	38
SPECIFIC GRAVITY:	1.28
DESIGN:	SPHERIC

 REGULAR POWER RANGE MINUS SPHERE
 REGULAR POWER RANGE PLUS SPHERE

E & O.E.